

Ref. : BA 1653.pas

Rev. : Initial

Date : 25/10/06

Page : 1/1

BALL VALVE FOR WATER METER WITH DRAIN COCK

BA 1653



Tecofi'
VALVE DESIGNER - FRANCE

APPLICATION

Ball valve for meter with drain cock (male).

GENERAL CHARACTERISTICS

Brass valve and ball.
Operating by lever with bleed screw.
BSP Male ends - PN 20.

CONSTRUCTION

6	1	Handling	Aluminium	
5	1	Packing flanged	PTFE	
4	2	Seat	PTFE	
3	1	Stem	Brass CuZn39Pb2	DIN: CuZn39Pb2 ASTM: B124 C37700 BS: 12164 CZ121
2	1	Ball	Chromed brass CuZn36Pb3	DIN: CuZn36Pb3 ASTM: B16 C36000 BS: 12164 CZ124
1	1	Body	Brass CuZn39Pb2	DIN: CuZn39Pb2 ASTM: B124 C37700 BS: 12164 CZ121
Pos.	Qty.	Description	Material	

DIMENSIONS

DN		DN1	L	H	P	Weight (kg)
mm	inch					
20	3/4"	3/4"	80	38,5	70	0,28
20	3/4"	1"	87	38,5	70	0,29

WORKING CONDITIONS

Maximum working pressure : 20 bar.
Maximum temperature : -30°C / +120°C.

Pressure test according to standards
EN 12266-1, DIN 3230, BS 6755 and ISO 5208 :
Body : 30 bar.
Seat : 22 bar.

STANDARDS

BSP threaded according to standard ISO 228-1.

