

Ref. : CA 4251.pas

Rev. : Initial

Date : 05/09/2016

Page : 1/1

FLANGED TYPE AXIAL CHECK VALVE

CA 4251



Tecofi'
VALVE DESIGNER - FRANCE



APPLICATION

General uses: pumping, irrigation, industry, clean water.

GENERAL CHARACTERISTICS

From DN 50 to DN 600.
Excellent tightness.
Low head loss.
Extremely reliable.
Simplicity in mounting and use.

CONSTRUCTION

7	1	Spring	Stainless steel 304
6	1	Bague	Bronze
5	1	Joint	EPDM
4	1	Axis	Stainless steel X20Cr13
3	1	Disc	Ductile iron
2	1	Cone	Ductile iron
1	1	Body	Ductile iron
Pos.	Q-ty	Description	Material

DIMENSIONS

DN		H	Ø D	Weight (kg)
mm	inch			
50	2"	125	165	6
65	2 1/2"	145	185	8
80	3"	155	200	12
100	4"	175	220	17
125	5"	200	250	23
150	6"	225	285	35
200	8"	275	340	60
250	10"	325	405	95
300	12"	375	460	130
350	14"	425	520	180
400	16"	475	580	240
450	18"	500	650	264
500	20"	587	715	380
600	24"	710	840	590

WORKING CONDITIONS

Maximum working pressure : 25 bar

Maximum temperature : -10°C / +80°C.


Test pressure according to EN 12266-1,
DIN 3230, BS 6755 et ISO 5208 :

Body : 37,5 bar.


Seat : 27,5 bar.

STANDARDS

Flanges drilled according to EN 1092-2 and
DIN 2501/1 : ISO PN25.



DN50-400



DN450-600