

Ref. : F3240TAMIS-IN

Rev. : Initial

Date : 08/01/2014

Page : 1/1

Screen for flanged type strainer F 3240EP PN16

F3240TAMIS-IN



Tecofi'
VALVE DESIGNER - FRANCE

APPLICATION

For all types of fluids.

GENERAL CHARACTERISTICS

Stainless steel screen.
Rolled, welded construction.

CONSTRUCTION

Stainless steel 304 body

DIMENSIONS

DN		L	Ø D	K	E	Bore diameters	Weight (kg)		
mm	inch								
15	1/2"	69	17	10	0.6	1	0.02		
20	3/4"	77.5	23				0.03		
25	1	97	27				0.045		
32	1"1/4	116.5	35				0.075		
40	1"1/2	91.2	42				0.1		
50	2"	105.2	52				0.13		
65	2"1/2	127.2	67			1.3	0.18		
80	3"	140.7	82				0.25		
100	4"	180.2	102				0.34		
125	5"	215.7	127				0.48		
150	6"	234.2	152	15	0.8	1.6	0.63		
200	8"	296.5	202				1.1		
250	10"	393.5	252				1.76		
300	12"	426	302				2.5		
350	14"	612	362				30	1.2	3.9
400	16"	689	410				40		5

WORKING CONDITIONS

Maximum working pressure: 16 bar (TS max + 140°C)

Test pressure according to EN 12266-1,
DIN 3230, BS 5154 and ISO 5208

STANDARDS

For use only with flanged type PN16 strainer F3240EP

